



RUGGED. RELIABLE. REAL.

ET18KX

FEATURES

- 4,500 LB Maximum Lifting Capacity
- 18,000 FT-LB Moment Rating
- Electric - Hydraulic Power
- Manual or Hydraulic Boom Extension 8-12 FT
- Manual Boom Extension 12-16 FT
- Continuous Power Rotation
- Meets ANSI B30.5 Safety Standards
- Meets OSHA 1910.180 Requirements

LIFTING CAPACITIES	
REACH (FT.)	CAPACITY (LBS.)
4	4,500
8	2,250
12	1,500
16	1,125

STANDARD EQUIPMENT

- Capacity Overload Shut-Off System
- Anti-Two-Blocking System
- 80 FT of 5/16" Aircraft-Quality Wire Rope
- Remote Control Pendant: 25 FT Cord and Quick Disconnect
- Load Block with Swivel Hook Safety Latch
- Master Disconnect Switch
- Battery Cable: 25 FT

MINIMUM REQUIREMENTS

- 10,500 LB GVWR Chassis
- Outriggers: Rear
- Electric Power Source: 12V DC

OPTIONAL EQUIPMENT

- Radio Remote Controls
- Electric/Hydraulic and Manual Outrigger Packages
- Mounting Pedestal for Platform Bodies
- Boom Rests

