



CRANE BODY VP60-165-DTF

Crane Capacity	8,000 - 12,000 lbs
Cab-Axle	120" CA
Ft-lbs Rating	66,000 ft.lbs.
Bed Length	14 ft. (165")
Tire Size	22.5" (DRW)
Crosstube	25100 / 27695
Min. GVWR	Class 5 - 19,500 lbs
Body Weight	5,000 lbs.
Model Number	Pro 12



SPECIFICATIONS

Compartment Height	44" / 60"
Compartment Depth	22"
Cargo Space Width	50"
SS/CS-1 Dimensions	31"W x 60"T
SS/CS-2 Dimensions	31"W x 50"T
SS/CS-3 Dimensions	12"W x 50"T
SS/CS-4 Dimensions	50"W x 24"T
SS/CS-5 Dimensions	25"W x 50"T
Main Body Material	14-ga Galvanneal
Compartment Bottoms	10-ga Galvanneal
Compartment Tops	12-ga HR treadplate
Inner Door Panels	0.063 Aluminum
Outer Door Panels	0.063 Aluminum
Wheel Panels	14-ga Galvanneal
Front Bulkhead	14-ga Galvanneal
Adjustable Shelving	14-ga Galvanneal
Bed Wall Liners	12-ga HR treadplate

Body Floor and Understructure

- 12-ga treadplate floor
- 10" high x 10 ga Grade 50 channel frame
- 12-ga Grade 50 underbelly plate

Powder Coat Finish

White

Standard Accessories

- 3-point whaletail compression door latches
- Gas cylinder type door holders
- Rubber rolled crown fenderettes installed
- Master Door Locking System
- Adhesive LED strip lights in all (10) compartments
 - Top and Sides
 - Top of Horizontal Compartment
- Strap Hinges
- 6,000 lb. Tie-Downs

STANDARD EQUIPMENT

- Workbench Bumper w/ Vise Plate
- 25100 Crosstube
- (4) LED Exterior Worklights
- White Powder Coat
- Bedliner (Cargo area, Compartment Tops, Walls, Bumper, Interior Tailgate)

APPLICABLE CRANE MODELS

- Up to Venturo HT66KX-25 12,000 lbs

CRANE BODY VP60-132-DTF

