

ELECTRIC - HYDRAULIC CRANES ET8KX



SPECIFICATIONS

Lifting Capacities:	3,200 lbs
Crane Rating:	8,000 ft-lbs
Mounting Space:	14" x 14"
Stowed Height:	26-1/4"
Rope Diameter:	1/4" @ 65'
Line Pull Speed	25 ft/min (Single-line)
	4 ft/min (Double-line)
Max. Single-line:	1,600 lbs
Max. Double-line:	3,200 lbs
Rotation:	360° Continuous
Power Supply Requirements:	Power Supply: Electric 12V DC Requirements: 12v DC Battery
Hydraulic Req:	Self-Contained w/ Power Unit
Boom Elevation:	-8° to +75°
Controls:	12V DC Non- Proportional
Boom Extension:	Power: 6' - 10' Manual: 10' - 14'
Weight:	650lbs
Minimum Vehicle Class:	Class 2 (8,000 lbs GVWR)
Optional:	- Non- Proportional - Proportional - Corded - Corded & Wireless



The Venturo ET8KX is a 8,000 ft-lb electric-hydraulic service crane with a 3,200 lb lifting capacity featuring 12V DC electric winch, hydraulic rotation, hydraulic boom elevation with a hydraulic extension and secondary manual extension. The ET8KX also has optional proportional controls which allow the operator additional control over speeds of the hydraulic functions.

FEATURES

- INDUSTRY LEADING IN ELECTRIC-HYDRAULIC CRANES
- POWERFUL DC ELECTRIC WINCH
The ET series winches combine a powerful permanent magnet DC motor with robust sealing with proven 3-stage, all-metal gear train. Permanent grease lubrication means years of trouble-free service.
- MANUAL CRANE OVERRIDE
Each ET series crane gives the user the ability to operate and stow the crane if there is power loss through the remote
- POWERFUL HYDRAULIC SLEW DRIVE
Driven from high quality durable electric motor
- COUNTER-BALANCE VALVE
Counterbalance valving in all cylinders for increase safety and protection during operation

